HOW TO TREAT YOUR V2



- Wash the jug at least 1-2 times a week.
- Keep cartridge away from soap unless empty.
- Plastic parts and glass jar are dishwasher safe.



- Pour while the reservoir is full.
- Put gaskets or black base in dishwasher.



国協議 INDICATOR

Want to know when to change your filter?
Visit phoxwater.com/app to get your indicator!

ACTIVATE YOUR GUARANTEE

Visit phoxwater.com/activate to activate your 12 month parts guarantee.



NEED HELP? service@phoxwater.com

HOW TO REACTIVATE AFTER A PERIOD OF NON-USE:

Soak in water during non-use and perform 2 run throughs before commencing use.

Household equipment for the treatment of drinking water. The pitcher filters the drinking water from the mains thanks to a cartridge that improves the taste of the water by reducing any unwanted substances that may be present.

Warning: this product requires regular periodic maintenance, including washing the jug and replacing the filter, in order to ensure the potability requirements of the treated drinking water and the maintenance of improvements as declared by the manufacturer.

In the event of a boil water notice or similar emergency, the filtered water should be boiled. Dispose of the used filter media in use when the boil water notice period is over.



$\rho h \delta x$

HOW TO SET UP YOUR

GLASS V2





SCAN FOR SET UP VIDEO OR VISIT PHOXWATER.COM/SETUP



Unscrew reservoir from glass jar and remove cartridge from reservoir. Wash each component of the jug



6 Half fill the glass jar with fresh cold water and soak cartridge for 6 minutes.

Fit the lid securely on to the

cartridge.






Take out one refill bag and one carbon felt bag from the pack.



7 Twist the cartridge into the reservoir and fill up. Allow 2 full reservoirs to filter before consuming water.



Take out the carbon felt disk and insert into the lid as shown.



Wash out the glass jar, as it may have deposits from step 7.



Open up your refill pack and pour into the cartridge.



When putting your jug back together, make sure you put the gasket back onto the jar to create a watertight seal.

YOU ARE NOW READY TO USE YOUR V2!